



Un design che privilegia freschezza e allegria senza dimenticare il comfort, è il biglietto da visita per questa seduta, ideale per qualsiasi ambiente, collettività.

Formata da una scocca in plastica, disponibile in diversi colori, ha il telaio nero, cromato, verniciato alluminio gofrato. Perfetta per l'home-office grazie alla scocca girevole con possibilità di regolazione in altezza.

A design that favours freshness and cheerfulness without forgetting comfort is the calling card for this chair, ideal for any community environment.

Formed of a plastic shell, available in various colours, it has a black, chrome-plated or embossed aluminium painted frame. Perfect for the home-office thanks to the swivel shell with height adjustment.

FLASH 160

Design: OMP R&D



FLASH LOOKS GREAT AND
IS PRACTICAL TO USE
WITH ITS BRIGHT ORIGINAL
COLOURS



FLASH 160 4 LEGS



FLASH 160 4 LEG STOOL



FLASH 160 ON 500 BENCH



FLASH 160

Design: OMP R&D

Sedia 4 gambe e sgabello con telaio in ferro nelle finiture cromato e verniciato, schienale in polipropilene caricato fibre di vetro con e senza braccioli, braccioli in polipropilene caricato fibra di vetro. Sedile da tappezzare in polipropilene e sotto sedile con fissaggio a scatto senza uso di viti in polipropilene, piedini fissi in polipropilene.

Nella versione sgabello 4 gambe, le anteriori e le posteriori sono in tubo tondo Ø 16 mm, spessore 2 mm, secondo norma UNI 10305-3, il fissaggio della scocca è realizzato con lamiera da 15 mm spessore 3 mm. Il poggiapiedi è in tondino Ø 11 mm FE360 E4FT-A6 CR (materiale per cromo) piegato e saldato a MIG. Per le specifiche relative alla versione panca vedi da pag. 231 in poi.

4-Leg chair and stool with metal frame in chromium-plated and painted finishes, fiberglass-filled polypropylene backrest with and without arms, fiberglass-filled polypropylene arms. Polypropylene seat (requires upholstery) and polypropylene seat outer with snap fitting (no screws), fixed polypropylene feet.

In the stool version with 4 legs, the front and rear legs are made of tubular steel Ø 16 mm, thickness 2 mm, in compliance with UNI 10305-3, shell fastening in 15 mm sheet metal, thickness 3 mm. The footrest is made of bent steel rod Ø 11 mm FE360 E4FT-A6 CR (for chromium plating), MIG welded. For the specifications of the bench version see from page 231 onwards.

Colori plastiche

Plastic colours



Nero
Black



Bianco
White



Grigio cemento
Cement grey



Arancione
Orange



Pistacchio
Pistachio



Blu zaffiro
Sapphire blue

Parti in metallo

Metal parts




Verniciato alluminio goffrato
Embossed painted aluminium




Cromato
Chromium plated

FLASH 160 4 LEGS



FLASH 160 4 LEG STOOL



FLASH 160 ON 500 BENCH

